



Certificate No.: 1207-6066

Applicant: Grande-Tek Flow Control Co., Ltd, Industrial Zone of Yunhe District, Fuyang Road,
CN- Cangzhou, Hebei

In accordance with our regulation ZW101 „general terms and conditions of the SGWA certification body water“ the SGWA certify the following serial products:

Rubric: Corrosion-resisting steel tubes and fittings
Denomination: GD-Press
Types: Press fittings made of stainless steel AISI 304 / 316L Ø 15-108 mm

For Pipes made of corrosion resistant steel 1.4401
15x1.0, 18x1.0, 22x1.2, 28x1.2, 35x1.5, 42x1.5, 54x1.5
76.1x2.0, 88.9x2.0, 108x2.0

DN: 12...100 PN: 16 tmax= 70°C

Certification Standard: SGWA ZW132 (01/18), DVGW W534 (2015)

Validity: 31.08.2022

Notes / Conditions:


The press fittings GD-Press can only be connected with tested pipes made of corrosion resistant steel 1.4401.

Fittings resistance coefficients Zeta are available on request!

The applicant is entitled to offer the above mentioned products as certificated by the SGWA and to use the above SGWA-conformity mark (publication in the list of certificates water).



accredited according to
SN EN ISO/IEC 17065

Swiss Gas and Water Industry Association
Certification body water

Javier Fernandez
Head

Rubric: Corrosion-resisting steel tubes and fittings

Denomination: GD-Press

Types	DN	PN	C°	Acoustic group	Losses kWh/24 h / ErP Class	Content Index	Metrological class
GDA500x Coupling SC Ø15-108 mm	12...100	16	70			9	
GDA501x Slip coupling KC Ø15-108 mm	12...100	16	70			9	
GDA50xx Reducer w. plain end RC	12...100	16	70			9	
GDA505x 90° Elbow 90E(A) Ø15-108 mm	12...100	16	70			9	
GDA507x 90° Elbow w. plain end 90E(B)	12...100	16	70			9	
GDA510x 45° Elbow 45E(A) Ø15-108 mm	12...100	16	70			9	
GDA512x 45° Elbow w. plain end 45E(B)	12...100	16	70			9	
GDA509x 90° Elbow w. plain ends 90P	12...100	16	70			9	
GDA514x 60° Elbow w. plain ends 60P	12...100	16	70			9	
GDA518x Tee T(S) Ø15-108 mm	12...100	16	70			9	
GDA5xxx Reducing Tee T(R)	12...100	16	70			9	
GDA523x Tee w. male thread end ETCT	12...32	16	70			9	
GDA52xx Tee w. female thread end ITCT	12...100	16	70			9	
GDA527x 90° Male elbow ETC90E Ø15-54 mm	12...50	16	70			9	
GDA529x 90° Female elbow ITC90E Ø15-35 mm	12...32	16	70			9	
GDA532x 90° Female Elbow w. wall plate	12...20	16	70			9	
GDA530x Flange w. pressing socket FC	12...100	16	70			9	
GDA53xx Adaptor w. union nut ZL Ø15-54 mm	12...50	16	70			9	
GDA53xx Adaptor w. male thread ETC	12...100	16	70			9	
GDA53xx Adaptor w. female thread ITC	12...65	16	70			9	
GDA542x Cap CAP Ø15-108 mm	12...100	16	70			9	
GDA54xx Adaptor union w. male thread ETCZ	12...50	16	70			9	
GDA54xx Adaptor union w. female thread ITCZ	12...50	16	70			9	
GDA517x Bridge B Ø15-28 mm	12...25	16	70			9	

Fittings resistance coefficients Zeta are available on request!